



Product Information

20W50 SL

A gasoline engine oil, formulated with solvent refined base oils and a well- balanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

Application

This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high Sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals

Specifications

Performance level:

ACEA A3/B4
API SL
MB 228.3

Typical Characteristics

Property	Unit	Typical Values
Density at 15 °C	kg/l	0,898
Viscosity -15 °C	mPa.s	7500
Viscosity 40 °C	mm ² /s	156,30
Viscosity 100 °C	mm ² /s	17,50
Viscosity Index		123
Flash Point COC	°C	230
Pour Point	°C	-30
Total Base Number	mgKOH/g	11,1
Sulphate Ash	%	1,43

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.