



Product information

5W30 SN

A synthetic universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which special additives are added to obtain the following properties:

- A fast cold start
- A safe lubrication film at high temperatures
- A very good detergency and dispersion
- A very strong protection against wear, corrosion and foaming

This synthetic universal "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

Performance level:

ACEA C2, C3
API SN
BMW Longlife-04
GM dexos 2
MB 229.51/229.52
VW 505.01

Typical Characteristics

5W30 SN		
Property	Unit	Typical Values
Density at 15 °C	kg/l	0.853
Viscosity -15 °C	mPa.s	6300
Viscosity 40 °C	mm ² /s	73
Viscosity 100 °C	mm ² /s	12.1
Viscosity Index		163
Flash Point COC	°C	242
Pour Point	°C	-36
Total Base Number	mgKOH/g	8
Sulphate Ash	%	0.79

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website.