

Product Information

Brake fluid DOT3

Description

Brake fluid DOT3 is a high boiling synthetic brake fluid which meets the requirements of the SAE J1703, FMVSS 116 DOT 3, ISO 4925, JIS K2233 and AS 1960.1 specifications. It is formulated from mixed poly-alkaline glycol ethers together with additives and corrosion inhibitors. It offers high level of protection against wear and corrosion

Application

Applicable for all hydraulic brake systems with drum or disk brakes requiring a synthetic brake fluid and where a brake fluid of the type DOT 3 is prescribed.

Specification

Performance level:
FMVSS 116 DOT 3
ISO 4925 Class 3
JASO JIS K2233 Class 3
SAE J1703

Typical Characteristics

		DOT3
Property	Unit	
Density @20 °C	g/ml	1.05
Boiling Point (reflux) , °C	°C	240
Wet Boiling Point, °C	°C	145
pH -50% in Ethanol Solution		7-11

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website.