Product Information

Coolant X 50% Green

Description

Coolant 50% is a "long life" OAT (Organic Additives Technology) automotive coolant based on Mono-ethylene-glycol and demineralized water with addition of additives to obtain the following properties:
- A perfect protection of all types of metals that are used in engines and cooling systems
- A neutral behavior towards seals, gaskets and hoses
- A very good resistance against formation of foam
- Nitrite, amine, phosphate and silicate free
- Colored Green

Application

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines.
This coolant is ready for use and protects against freezing down to -38°C.

Specification

Performance level:
ASTM D3306/D4985/D6210
Chrysler MS 9176
Cummins 85T8-2
DAF 74002
Detroit Diesel
Ford WSS-M97B44-D
GM 6277M
John Deere H 24 B1 & C1
Mack 014GS 17004
MAN 324 Type SNF
MB 326.3
Leyland Trucks LTS 22 AF 10
Renault 41-01-001/--S Type D
Scania TB 1451
Volkswagen VW TL 774-F (G12 Plus)
Volvo VCS

Typical Characteristics

Coolant 50%		
Property	**Unit**	
Density at 15 °C, kg/l	Kg/l	1,070
Crystallization point, °C	°C	-38