



Product information HD50 – CF-4

This engine OIL can be used under the most difficult operating conditions (highways, congested city traffic, etc.) for every season. Formulated for gasoline and diesel engines used in city and suburban driving conditions.

It provides

- Maximum cleanliness
- Reduced engine maintenance costs
- Superior thermo-oxidative stability

This engine Oil can be used in older trucks and buses as well as for cost effective lubrication where an API CF4 lubricant is required

Performance level:

API CF-4

SAE 50		
Property	Unit	Typical Values
Density at 15 °C	kg/l	0.915
Viscosity -15 °C	mPa.s	6200
Viscosity 40 °C	mm ² /s	205
Viscosity 100 °C	mm ² /s	19.5
Viscosity Index		105
Flash Point COC	°C	220
Pour Point	°C	-20
Total Base Number	mgKOH/g	12
Sulphate Ash	%	1.1

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website.