



SNA GmbH

Hochleistungs - Schmierstoffe



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Description

A synthetic universal motor oil, that suspends particles, helping the engine to perform at its peak longer by fighting power robbing deposits and continues to provide low volatility to keep the engine running at peak power longer.

Main advantages :

- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming
- a very efficient engine performance

Application

This synthetic motor oil is recommended for use in petrol engines, with or without turbo-charging, in passenger cars and SUV's.

Specification

Performance level:

ACEA A1/B1
API SN
Porsche A40
VW 505.00
VW 502.00

Typical Characteristics

5W20 SN		
Property	Unit	Typical Values
Density at 15 °C	kg/l	0.848
Viscosity -15 °C	mPa.s	6200
Viscosity 40 °C	mm ² /s	49.35
Viscosity 100 °C	mm ² /s	8.88
Viscosity Index		161
Flash Point COC	°C	200
Pour Point	°C	-38
Total Base Number	mgKOH/g	8,0
Sulphate Ash	%	0.79

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

You can download a recent material safety data sheet of this product on our website.